

Claims:

1. A system for implementing a Fast Fourier Transform (FFT) in a broad bandwidth, high data rate communications application, the system comprising:
means to divide the bandwidth into sub-bands; and
means to implement the FFT separately for each sub-band.
2. The system as defined in claim 1 further including pass band filters to isolate desired sub-band frequencies.
3. The system as defined in claim 2 having a modulator to process each sub-band separately prior to implementation of the FFT and up-sampling means in advance of the filter to up-sample a signal to the desired sampling rate.
4. The system as defined in claim 3 wherein said system is in a transmitter for transmitting Discrete Multi-tone (DMT) signals in a Digital Subscriber Line (DSL) application.
5. The system as defined in claim 3 for use in a Very high rate Digital Subscriber Line (VDSL) application.
6. The system as defined in claim 2 wherein said means to implement the FFT is an Inverse FFT (IFFT).
7. The system as defined in claim 6 wherein said system is in a receiver for receiving DMT signals in DSL application.
8. The system as defined in claim 6 for use in a receiver in a VDSL application.
9. A method of implementing a Fast Fourier Transform (FFT) in a broad bandwidth, high data rate communications application, the method comprising:
dividing the bandwidth into sub-bands; and

implementing the FFT separately for each sub-band.

10. The method as defined in claim 9 further including the step of providing pass band filters to isolate desired sub-band frequencies.
11. The method as defined in claim 9 wherein said FFT is implemented for only a single side band of said sub-bands.
12. The method of claim 11 wherein a single side band filter is used.
13. The method as defined in claim 10 including the step of providing a modulator to process each sub-band separately prior to implementation of the FFT.
14. The method as defined in claim 13 wherein an up-sampling means in advance of the filter up-samples a signal to the desired sampling rate.
15. The method as defined in claim 9 for use in a frequency division multiplexing application wherein a variable sized FFT is used for each individual band.
16. The method of claim 15 wherein variable up and down sampling rates are used for each individual band.

0942623 08340
FOI 80 2292450